Department of Energy

impacts, and technical aspects of the siting process. After notifying affected States and affected Indian tribes that potentially acceptable sites have been identified, or that a site has been approved for characterization, the DOE shall seek to enter into binding written agreements with such affected States or affected Indian tribes in accordance with the requirements of the Act. The DOE shall also consult, as appropriate, with other Federal agencies.

§ 960.3-4 Environmental impacts.

Environmental impacts shall be considered by the DOE throughout the site characterization, site selection, and repository development process. The DOE shall mitigate significant adverse environmental impacts, to the extent practicable, during site characterization and repository construction, operation, closure, and decommissioning.

Subpart C—Postclosure Guidelines

§ 960.4 Postclosure guidelines.

The guidelines in this subpart specify the factors to be considered in evaluating and comparing sites on the basis of expected repository performance after closure. The postclosure guidelines are separated into a system guideline and eight technical guidelines. The system guideline establishes waste containment and isolation requirements that are based on NRC and EPA regulations. These requirements must be met by the repository system, which contains natural barriers and engineered barriers. The engineered barriers will be designed to complement the natural barriers, which provide the primary means for waste isolation.

§ 960.4-1 System guideline.

(a) Qualifying Condition. The geologic setting at the site shall allow for the physical separation of radioactive waste from the accessible environment after closure in accordance with the requirements of 40 CFR part 191, subpart B, as implemented by the provisions of 10 CFR part 60. The geologic setting at the site will allow for the use of engineered barriers to ensure compliance with the requirements of 40 CFR part 191 and 10 CFR part 60 (see appendix I of this part).

§ 960.4-2 Technical guidelines.

The technical guidelines in this subpart set forth qualifying, favorable, potentially adverse, and, in five guidelines, disqualifying conditions on the characteristics, processes, and events that may influence the performance of a repository system after closure. The favorable conditions and the potentially adverse conditions under each guideline are not listed in any assumed order of importance. Potentially adverse conditions will be considered if they affect waste isolation within the controlled area even though such conditions may occur outside the controlled area. The technical guidelines that follow establish conditions that shall be considered in determining compliance with the qualifying condition of the postclosure system guideline. For each technical guideline, an evaluation of qualification or disqualification shall be made in accordance with the requirements specified in subpart B.

§ 960.4-2-1 Geohydrology.

- (a) Qualifying condition. The present and expected geohydrologic setting of a site shall be compatible with waste containment and isolation. The geohydrologic setting, considering the characteristics of and the processes operating within the geologic setting, shall permit compliance with (1) the requirements specified in §960.4–1 for radionuclide releases to the accessible environment and (2) the requirements specified in 10 CFR 60.113 for radionuclide releases from the engineered-barrier system using reasonably available technology.
- (b) Favorable conditions. (1) Site conditions such that the pre-waste-emplacement ground-water travel time along any path of likely radionuclide travel from the disturbed zone to the accessible environment would be more than 10,000 years.
- (2) The nature and rates of hydrologic processes operating within the geologic setting during the Quaternary Period would, if continued into the future, not affect or would favorably affect the ability of the geologic repository to isolate the waste during the next 100,000 years.